



The product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 11.5 cubic feet (87 gallons)
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -4°F up to +120°F (with reduced specifications)
- Refrigeration system includes BD series 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system
- Versions with automatic cooling / heating operation are available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). They maintain consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP
- AC/DC power supplies (input voltage 100-240Vac 50-60 Hz) available as accessories

Available versions:

- NDN down to +32°F
- NDH from +86°F to +32°F
- FDN down to -6°F
- FDH from +86°F to -6°F
- XFDN down to -22°F



easy cooling, smart moving

Model name	F0330/NDN	F0330/NDH	F0330/FDN	F0330/FDH	F0330/XFDN
EE article nr.	816008/00	816008/02	816008/01	816008/03	816008/04
Gross capacity ft3 (gal)	11.5 (87)	11.5 (87)	11.5 (87)	11.5 (87)	11.5 (87)
Temperature range (°F)*	> +32°F	+86°F to +32°F	> -6°F	+86°F to -6°F	> -22°F
Automatic cooling/heating	no	yes	no	yes	no
Voltage	12-24Vdc	12-24Vdc	12-24Vdc	12-24Vdc	12Vdc
Peak Amps (@12Vdc)	10	10	18	18	25
Fuse on DC cord	30A	30A	30A	30A	50A
External dimensions (inches)	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8
Weight (Lbs)	176.3	182.9	182.9	189.6	198.4
PU insulation (inches)	3.9	3.9	3.9	3.9	3.9
"K" insulation factor	0.27 W/m²K	0.27 W/m²K	0.27 W/m²K	0.27 W/m²K	0.27 W/m²K
Compressor (model)	BD50F	BD50F	BD80F	BD80F	BD220CL
Refrigerant gas (type)	R134a	R134a	R134a	R134a	R404A
Refrigerant gas (grams)	96	96	130	130	250
Battery cut-out/cut-in	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	11Vdc-12,3Vdc
Optional AC/DC power supply	560019/00	560019/00	560020/00	560020/00	560020/00
AC/DC power supply input	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz

*with ambient temperature +86°F



F0330 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 11.5 cubic feet (87 gallons)
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from -4°F up to +120°F (with reduced specifications)
- Refrigeration system includes BD series 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system
- Versions with automatic cooling / heating operation are available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). They maintain consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP
- AC/DC power supplies (input voltage 100-240Vac 50-60 Hz) available as accessories

Available versions:

- NDN down to +32°F
- NDH from +86°F to +32°F
- FDN down to -6°F
- FDH from +86°F to -6°F
- XFDN down to -22°F



easy cooling, smart moving

www.coldtainer.com

F0330 PRODUCT INFO

Model name	F0330/NDN	F0330/NDH	F0330/FDN	F0330/FDH	F0330/XFDN
EE article nr.	816008/00	816008/02	816008/01	816008/03	816008/04
Gross capacity ft3 (gal)	11.5 (87)	11.5 (87)	11.5 (87)	11.5 (87)	11.5 (87)
Temperature range (°F)*	> +32°F	+86°F to +32°F	> -6°F	+86°F to -6°F	> -22°F
Automatic cooling/heating	no	yes	no	yes	no
Voltage	12-24Vdc	12-24Vdc	12-24Vdc	12-24Vdc	12Vdc
Peak Amps (@12Vdc)	10	10	18	18	25
Fuse on DC cord	30A	30A	30A	30A	50A
External dimensions (inches)	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8	40.2 x 39.4 x 35.8
Weight (Lbs)	176.3	182.9	182.9	189.6	198.4
PU insulation (inches)	3.9	3.9	3.9	3.9	3.9
"K" insulation factor	0.27 W/m ² K	0.27 W/m ² K	0.27 W/m ² K	0.27 W/m ² K	0.27 W/m ² K
Compressor (model)	BD50F	BD50F	BD80F	BD80F	BD220CL
Refrigerant gas (type)	R134a	R134a	R134a	R134a	R404A
Refrigerant gas (grams)	96	96	130	130	250
Battery cut-out/cut-in	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	9.6Vdc-10.9Vdc	11Vdc-12,3Vdc
Optional AC/DC power supply	560019/00	560019/00	560020/00	560020/00	560020/00
AC/DC power supply input	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz	100-240Vac 50-60 Hz

*with ambient temperature +86°F

